

1. PERFORMANCE


- | | | |
|--------------------------|--|-----------|
| 1) Measuring range | : 1-10 ppm | 0.5-5 ppm |
| Number of pump strokes | : 1/2 (50mℓ) | 1 (100mℓ) |
| 2) Sampling time | : 1 minute/1 pump stroke | |
| 3) Detectable limit | : 0.2 ppm (100mℓ) | |
| 4) Shelf life | : 2 years | |
| 5) Operating temperature | : 0 ~ 40 °C | |
| 6) Reading | : The tube scale is calibrated based on Methyl mercaptan at 1 pump stroke and the tube has the same sensitivity for Ethyl mercaptan. | |
| 7) Colour change | : Pale yellow → Pink | |

2. RELATIVE STANDARD DEVIATION

RSD-low : 10% RSD-mid. : 5% RSD-high : 5%

3. CHEMICAL REACTION

By reacting with Mercuric chloride, Hydrogen chloride is produced and PH indicator is discoloured.



4. CALIBRATION OF THE TUBE

PERMEATION TUBE METHOD

5. INTERFERENCE AND CROSS SENSITIVITY

Substance	Interference	Coexistence
Arsine	Similar stain is produced.	Higher readings are given.
Hydrogen selenide	∕	∕
Phosphine	∕	∕
Hydrogen sulphide	∕	∕
Hydrogen cyanide	Whole reagent is discoloured to Red.	∕
Sulphur dioxide		Whole reagent is changed to Pale red, but Pink stain indicates Mercaptans conc.

(NOTE)

In case of 1/2 pump strokes, following formula is available for the actual concentration.

Actual concentration = 2 × Reading value